

PRIME PANEL PERFORMANCE ATTACHMENT 21.5” THE MULTITOUCH PANEL PC FOR DEMANDING TASKS

FACT SHEET

- IPC easy to configure in hardware and software
- Flexible and extensive connectivity
- High operational safety by robust system design and IP65



Housing

Passive, fanless cooling.
Modern design, "form follows function".
Optional with logo and color ident.



Glass Front


Optimum readability, low reflections.
Scratch-resistant.
Easy to clean.



Touch

High operational safety - even under disturbing influence.
EMC-stable 4-finger operation, glove operation (cat. 1) pre-parameterized.
Specific parameterization such as palm suppression or working gloves inhouse.

THE MODULAR SYSTEM PRIME CUBE®



Modular

Customized solutions of industrial computer technology with all advantages of standard products: Validated platforms, short development process, optimum price-performance ratio.



High Quality

For 24/7 operation in an industrial environment.
Reliable and robust.
Long-term available (10 years), with 36 months of warranty.



Application-oriented & Customizable

BASE / STYLE / CUSTOM

We are your partner in the complete solution process of industrial computer technology.

From sensor application to tool monitoring in the machine and from embedded computing systems to a future-oriented IoT gateway concept we represent all product steps with our product brands Prime Cube® and BK Mikro®. At our headquarters in Neuhausen ob Eck (Baden-Württemberg) our 170 employees develop and manufacture customized computer systems: from hardware and software to assemblies and complete systems - innovative force "Made in Germany".



PRIME PANEL PERFORMANCE ATTACHMENT 21.5"

TECHNICAL DATA

prime
cube®

DESIGN		PRIME PANEL PERFORMANCE ATTACHMENT 21.5"
Model Code		PPI1000AD_215
Dimensions (WxHxD)		538.6 x 330.1 x 129 mm
Weight		12.5 kg
Housing		Aluminium front frame, powder-coated. Aluminium rear panel, powder-coated. Aluminium computer core with heat sink, anodized. Hardened and AR-coated front glass. Designed for mounting to a support arm system.
Protection Class		IP65 acc. EN 60529 all around.
Display	Size	FHD display, 1920 x 1080 px, 16:9.
	Luminance (typ.)	350 cd/m ²
	Contrast Ratio (typ.)	1000
	Viewing Angle (typ.)	89/89/89/89 °
	Lifetime Lighting (min.)	50.000 h
Touch		Projected Capacitive Touch (PCT), 4-finger operation, up to 10-finger operation optional. Specific parameterization possible inhouse.
Processor		Intel® CELERON™ G4900T 8th Gen Intel® Core™ i3-8100T; i5-8500T; i7-8700T; 9th Gen Intel® Core™ optional.
Working Memory		Up to 2 x 16 GB DDR4-2666; 2 x 32 GB optional. 2x SODIMM, dual channel
Mass Storage		1x M.2 Key-M: 64 GB - 512 GB, flash memory 1x 2.5" SSD: 64 GB - 512 GB, flash memory or 1 TB HDD, Further memory sizes and flash technologies available.
Extensions		1x mPCIe full-/half size 1x PCIe Slot x16 1x DSUB 9 pol
Removable Storage (optional)		1x CFast holder. Optional incl. CF-card.
Interfaces (Mainboard)		2x GbE LAN, separate controllers, Intel® I219-LM & I210-AT 4x USB 2.0 1x USB 3.1 stick socket 2x USB 3.1 Gen. 1 2x USB 3.1 Gen. 2 1x RS232 2x PS/2 1x line in; 1x line out 2x DisplayPort 1x DVI-D 1x 2-fold USB 3.1, external
Interfaces (extendable)	DSUB 9 pol	1x RS232/422/485 (standard configuration)
	mPCIe	2x GbE LAN, separate controllers, Intel® I210 1x CAN, 2-fold DSUB 9 pol (Profibus, Profinet and further fieldbusses feasible) 1x WLAN and BLUETOOTH (integrated at front side or external antennae) 1x mobile radio
	PCIe-Slot Bracket	1x USB 2.0 2x USB 3.1 Gen. 1
Battery		Buffer battery based
Voltage Supply		24 V DC (18 ... 36 V DC), galvanically isolated
Operating System		Windows 10 IoT Enterprise 2019 LTSC LINUX 64 bit: Debian 10 distribution
Ambient Temperature*		-10 °C ... +45 °C with natural convection (up to +40 °C when using a HDD) -10 °C ... +50 °C ** from 0.4 m/s air flow (up to +45 °C when using a HDD)
Storage Temperature		-20 °C ... +60 °C
Humidity		10% ... 90%, non-condensing
EMC Immunity		Industrial area acc. EN 55024 & EN 61000-6-2
EMC Emission		Industrial area acc. EN 55032 class A
Shock		15 g: 11 ms and 25 g: 6 ms acc. DIN EN60068-2-27
Vibration		2 ... 9 Hz: 3.5 mm amplitude, 9 ... 200 Hz: 1 g acc. EN 60068-2-6
Warranty		36 months
Approvals		CE; UL in testing; acc. UL 61010-2-201 & CSA C22.2 no. 61010-2-201


* Functional system test at maximum ambient temperature and the highest possible internal heat load.

** not evaluated by UL.

Please find dimensional drawings as downloads on our [website](#). 3D-models on request via e-mail to vertrieb@schubert-system-elektronik.de.

Version 1.08 / 2021 © Schubert System Elektronik GmbH. Alle Rechte und Änderungen bleiben vorbehalten. All data are non-binding and do not ensure any properties. Pictures/representations may also include special equipment or accessories. We assume no liability for printing errors. The company names, names and logos used are largely protected by copyright and/or trademarks, even if not explicitly marked as such. All product names used are brand names and/or trademarks of the respective manufacturers.

PRIME PANEL PERFORMANCE ATTACHMENT 21.5” CIRCUIT DIAGRAM



Please find dimensional drawings as downloads on our [website](#). 3D-models on request via e-mail to vertrieb@schubert-system-elektronik.de.

Version 1.08 / 2021 © Schubert System Elektronik GmbH. All rights and modifications reserved. All data are non-binding and do not ensure any properties. Pictures/representations may also include special equipment or accessories. We assume no liability for printing errors. The company names, names and logos used are largely protected by copyright and/or trademarks, even if not explicitly marked as such. All product names used are brand names and/or trademarks of the respective manufacturers.