








# Embedded Fanless System



		UNO		UNO	UNO	
Back Panel Motherboard I/O		2I260A-DH26  2I260A-CH26 			3V900D-V3G  3V900D-C4G 	
Motherboard		2I260A-DH26	2I260A-CH26	3V900A/C	3V900D-C4G	3V900D-V3G
System Dimension (WxDxH)		180W x 125D x 42H mm		180W x 125D x 42H mm	180W x 125D x 42H mm	
Weight (Incl. M/B)		1 kg		1 kg	1 kg	
CPU		Intel Cedarview-M N2600 1.6Ghz		VIA Nano™ Processor 1 GHz	VIA Nano™ Processor 1 GHz	
Chipset		Intel Cedarview-M + NM10		VIA VX900	VIA VX900	
Memory	Type / Capacity	DDR3 800 MT/s, Max up to 2GB		DDR3 1066 MT/s, Max up to 4GB	DDR3 1066 MT/s, Max up to 4GB	
	On board memory	2GB		N/A	N/A	
SSD Storage	CF (CFast)	N/A		CFast	CFast	
	mSATA	Optional		N/A	Optional	
	On Board SSD	Optional		Optional	Optional	
HDD Space		2.5" HDD X1		2.5" HDD x 1	2.5" HDD x 1	
VGA		N/A	Optional	Yes	N/A	Yes
DVI/HDMI		DVI & HDMI	HDMI	HDMI	N/A	
USB 2.0		2	4	2	2	3
PS2 KB/MS		N/A		Optional	N/A	
COM		N/A	1	N/A	1	N/A
Mini PCIe		2		2	2	
SIM Card Holder		Optional		1	1	
GPIO		4DI/4DO (optional)		8DI/8DO (optional)	8DI/8DO (optional)	
Ethernet		1 x PoE GbE		1 x GbE	4 x GbE	3 x GbE
Mic-in / Line-out		Line-out / Mic-in	Line-out	Yes	Optional	
Power Input		DC +12V		DC +12V	DC +12V	
Expansion		3G, GPS, Bluetooth, WI-FI		3G, GPS, Bluetooth, WI-FI	3G, GPS, Bluetooth, WI-FI	
Operating Temp		0~45°C for HDD ,0~50°C for mSATA		0~45°C for HDD, 0~50°C for CFast	0~45°C for HDD, 0~50°C for CFast	
Operating Humidity		5~95% @ 60°C, non-condensing		5%~95% @ 60°C, noncondensing	5%~95% @ 60°C, noncondensing	

- Car PC
- Networking
- POS / Automation
- DVR
- Digital Signage / Thin Client
- Embedded System
- Panel PC